



Modern decorative luminaire for LED light sources.

#### TECHNICAL DATA

**Mounting:** stand-alone  
**Body:** plastic, elements of varnished light alloys and glass

**Colour:** white

**Diffuser:** acrylic (PMMA)

#### ELECTRICAL DATA

**Power supply efficiency:** 80%

**Power:** 220-240V 50/60Hz

**Includes light source:** yes

**Type of equipment:** DALI

#### OPTICAL DATA

**Electrical connection:** max 5x0,75 mm<sup>2</sup> wire

**Light distribution:** rotationally-symmetric

**Way of lighting:** direct

#### GENERAL DATA

**Operating temperature range:** 0° C ... +40° C

**Additional information:** A leg made of painted wood or varnished aluminum.

**Other remarks:** leg of the luminaire in the form of a tripod


**Warranty:** 5 years

**Application:** hotels, residences, interiors



Code	Luminaire power [W]	Lumen luminaire [lm]	Efficacy [lm/W]	Colour temperature [K]	CRI/Ra
260021.3L010.011	11	760	69	3000	80

Code	Dimensions [mm] L W	Net weight [kg]
260021.3L010.011	480 280	1.8



#### OTHER PICTURES



Designed by LUG Design Team

Luminous flux tolerance +/- 10%.

Power tolerance +/- 5%.

Lighting beam, light intensity distribution and light efficiency were examined in accordance with the EN ISO 17025:2005 norm for EN13032 norm series and the LM-79 norm.

Date of issue: 15-6-2018

The LUG Company reserves right to introduce any construction changes and improvements into the lighting luminaires