

220-240V
50/60 HzIP
20

Modern downlight luminaire for LED light sources for plaster board ceilings.

TECHNICAL DATA

Mounting: in the ceiling, with mounting brackets (included)

Body: powder painted steel sheet, projector rings made of aluminum

Colour: black and white

ELECTRICAL DATA

Power: 220-240V 50/60Hz

Includes light source: yes

Type of equipment: ED

OPTICAL DATA

Way of lighting: direct

GENERAL DATA

Lifetime (L70B50): 80 000 h

Available on request: źródła metalohalogenkowe (na zamówienie), DALI

Additional information: The possibility of using one or more power supplies in the luminaire.

Warranty: 5 years

Application: offices, conference rooms, reception desks, shopping centers, car showrooms, boutiques



Code	Beam angle	Power LED [W]	Luminaire power [W]	Lumen LED [lm]	Lumen luminaire [lm]	Efficacy [lm/W]	Colour temperature [K]	CRI/Ra
200033.5L101.31	24°	17,5	21	1560	1560	74	4000	92
200033.5L102.31	24°	17,5	21	1430	1430	68	3000	92
200033.5L103.31	40°	17,5	21	1560	1560	74	4000	92
200033.5L104.31	40°	17,5	21	1430	1430	68	3000	92

Code	Dimensions [mm] L W H D1 D2	Mounting dimensions [mm] L W H D	Pallet quantity	Quantity in package	Net weight [kg]
200033.5L101.31	274 259 170 170 184	185 175 190 1.5	96	1	2.5
200033.5L102.31	274 259 170 170 184	185 175 190 1.5	96	1	2.5
200033.5L103.31	274 259 170 170 184	185 175 190 1.5	96	1	2.5
200033.5L104.31	274 259 170 170 184	185 175 190 1.5	96	1	2.5

