



Modern downlight luminaire for LED light sources for plaster board ceilings.

TECHNICAL DATA

Mounting: in the ceiling, with mounting brackets (included)
Body: powder painted steel sheet, projector rings made of aluminum

ELECTRICAL DATA

Colour: black and white
Power: 220-240V 50/60Hz

Includes light source: yes

OPTICAL DATA

Type of equipment: ED

GENERAL DATA

Way of lighting: direct

Available on request: źródła metalohalogenkowe (na zamówienie), DALI

Additional information: The possibility of using one or more power supplies in the luminaire.

Warranty: 5 years

Application: offices, conference rooms, reception desks, shopping centers, car showrooms, boutiques



| Code | Beam angle | Power LED [W] | Luminaire power [W] | Lumen LED [lm] | Lumen luminaire [lm] | Efficacy [lm/W] | Colour temperature [K] | CRI/Ra |
|-----------------|------------|---------------|---------------------|----------------|----------------------|-----------------|------------------------|--------|
| 200033.5L201.32 | 24° | 35 | 42 | 3120 | 3120 | 74 | 4000 | 92 |
| 200033.5L202.32 | 24° | 35 | 42 | 2860 | 2860 | 68 | 3000 | 92 |
| 200033.5L203.32 | 40° | 35 | 42 | 3120 | 3120 | 74 | 4000 | 92 |
| 200033.5L204.32 | 40° | 35 | 42 | 2860 | 2860 | 68 | 3000 | 92 |

| Code | Dimensions [mm] L W H D1 D2 | Mounting dimensions [mm] L W H D | Pallet quantity | Quantity in package | Net weight [kg] | W | L | H | D1 | D2 |
|-----------------|--------------------------------|-------------------------------------|-----------------|---------------------|-----------------|---|---|---|----|----|
| 200033.5L201.32 | 434 259 170 170 344 | 350 175 190 1.5 | 42 | 1 | 3.7 | | | | | |
| 200033.5L202.32 | 434 259 170 170 344 | 350 175 190 1.5 | 42 | 1 | 3.7 | | | | | |
| 200033.5L203.32 | 434 259 170 170 344 | 350 175 190 1.5 | 42 | 1 | 3.7 | | | | | |
| 200033.5L204.32 | 434 259 170 170 344 | 350 175 190 1.5 | 42 | 1 | 3.7 | | | | | |

Designed by LUG Design Team

Luminous flux tolerance +/- 10%.
 Power tolerance +/- 5%.

Lighting beam, light intensity distribution and light efficiency were examined in accordance with the EN ISO 17025:2005 norm for EN13032 norm series and the LM-79 norm.

Date of issue: 15-6-2018

The LUG Company reserves right to introduce any construction changes and improvements into the lighting luminaires