



220-240V  
50/60 Hz



IP  
20



Modern downlight luminaire for LED light sources for plaster board ceilings.

#### TECHNICAL DATA

**Mounting:** in the ceiling, with mounting brackets (included)

**Body:** powder painted steel sheet, projector rings made of aluminum

**Colour:** black and white

#### ELECTRICAL DATA

**Power:** 220-240V 50/60Hz

**Includes light source:** yes

**Type of equipment:** ED

#### OPTICAL DATA

**Way of lighting:** direct

#### GENERAL DATA

**Available on request:** źródła metalohalogenowe (na zamówienie), DALI

**Additional information:** The possibility of using one or more power supplies in the luminaire.

**Warranty:** 5 years

**Application:** offices, conference rooms, reception desks, shopping centers, car showrooms, boutiques



Code	Beam angle	Power LED [W]	Luminaire power [W]	Lumen LED [lm]	Lumen luminaire [lm]	Efficacy [lm/W]	Colour temperature [K]	CRI/Ra
200033.5L401.35	24°	70	83	6240	6240	75	4000	92
200033.5L402.35	24°	70	83	5720	5720	69	3000	92
200033.5L403.35	40°	70	83	6240	6240	75	4000	92
200033.5L404.35	40°	70	83	5720	5720	69	3000	92

Code	Dimensions [mm] L W H D1 D2	Mounting dimensions [mm] L W H D	Pallet quantity	Quantity in package	Net weight [kg]
200033.5L401.35	434 426 170 344 338	350 345 190 1.5	24	1	6.9
200033.5L402.35	434 426 170 344 338	350 345 190 1.5	24	1	6.9
200033.5L403.35	434 426 170 344 338	350 345 190 1.5	24	1	6.9
200033.5L404.35	434 426 170 344 338	350 345 190 1.5	24	1	6.9

