



220-240V
50/60 Hz



IP
20



Suspended decorative luminaire for LED light sources.

TECHNICAL DATA

Mounting: suspended, on wire suspension (included)

Body: powder painted aluminum profile, top cover made of anodized aluminum

Colour: ecru

Diffuser: opal plexiglass (PLX)

ELECTRICAL DATA

Power: 220-240V 50/60Hz

Includes light source: yes

Type of equipment: ED

OPTICAL DATA

Way of lighting: direct-indirect

GENERAL DATA

Available on request: DALI

Additional information: The possibility of using one or more power supplies in the luminaire.

Warranty: 5 years

Application: offices, conference rooms, reception desks, shopping centers, car showrooms, boutiques



Code	Beam angle	Power LED [W]	Luminaire power [W]	Lumen LED [lm]	Lumen luminaire [lm]	Colour temperature [K]	CRI/Ra
240010.5L01.12	24°	3x17,5W + 5x10W	121	4290+5000	4290 + 3750	3000	92
240010.5L02.12	24°	3x17,5W + 5x10W	121	4680+5000	4680 + 3750	4000	92
240010.5L03.12	40°	3x17,5W + 5x10W	121	4290+5000	4290 + 3750	3000	92
240010.5L04.12	40°	3x17,5W + 5x10W	121	4680+5000	4680 + 3750	4000	92

Code	Dimensions [mm] L W H	Mounting dimensions [mm] L	Pallet quantity	Quantity in package	Net weight [kg]
240010.5L01.12	1600 254 91	1360	2	1	7.0
240010.5L02.12	1600 254 91	1360	2	1	7.0
240010.5L03.12	1600 254 91	1360	2	1	7.0
240010.5L04.12	1600 254 91	1360	2	1	7.0

