

220-240V
50/60 HzIP
20

Decorative downlight luminaire, adapted for tool-free assembly, for suspended ceilings, for LED light sources. The luminaire in round version with different angles of light distribution.

TECHNICAL DATA**Mounting:** in the ceiling, with mounting brackets (included)**Body:** aluminum**Colour:** white**ELECTRICAL DATA****Power:** 220-240V 50/60Hz**Includes light source:** yes**Type of equipment:** ED**OPTICAL DATA****Light distribution:** rotationally-symmetric**Way of lighting:** direct**Reflector:** white**GENERAL DATA****Lifetime (L80B10):** 60 000 h**Warranty:** 5 years**Application:** public utility facilities, delicatessen, supermarkets, shopping centers, offices, car showrooms, pathways, halls, classrooms, corridors



Code	Power LED [W]	Luminaire power [W]	Lumen LED [lm]	Lumen luminaire [lm]	Efficacy [lm/W]	Colour temperature [K]	CRI/Ra
030601.5L01.3X1	5	6	700	600	100	3000	≥80
030601.5L02.3X1	5	6	700	600	100	4000	≥80
030551.5L01.3X1	11	14	1600	1450	104	3000	≥80
030551.5L02.3X1	11	14	1600	1450	104	4000	≥80
030551.5L03.3X1	14	17	2000	1800	106	3000	≥80
030551.5L04.3X1	14	17	2000	1800	106	4000	≥80
030561.5L01.3X1	21	24	3200	2900	121	3000	≥80
030561.5L02.3X1	21	24	3200	2900	121	4000	≥80
030561.5L03.3X1	28	31	4250	3800	123	3000	≥80
030561.5L04.3X1	28	31	4250	3800	123	4000	≥80

030551.5L01.3 ☐ 1

Beam angle

- 1 narrow
- 2 medium
- 3 wide

Code	Dimensions [mm] W H	Mounting dimensions [mm] ØS
030601.5L01.3X1	55 47	48
030601.5L02.3X1	55 47	48
030551.5L01.3X1	100 68	90
030551.5L02.3X1	100 68	90
030551.5L03.3X1	100 68	90
030551.5L04.3X1	100 68	90
030561.5L01.3X1	160 88	147
030561.5L02.3X1	160 88	147
030561.5L03.3X1	160 88	147



Luminous flux tolerance +/- 10%.

Power tolerance +/- 5%.

Up-to-date product info and General Warranty Terms available on our website www.luglightfactory.com

Code	Dimensions [mm] W H	Mounting dimensions [mm] ØS
030561.5L04.3X1	160 88	147

OTHER PICTURES



ø100 mm



ø50 mm