

LUMINAIRE PHOTOMETRIC TEST REPORT

8765 CTLS MILO LED WHITE 15W, 4000K, ANGLE 24°



Description Lines

Manufacturer:	NOWODVORSKI LIGHTING
Model name:	8765 CTLS MILO LED WHITE 15W,4000K,ANGLE24
File name:	8765 CTLS MILO LED WHITE 15W,4000K,ANGLE24.ltd
Date:	2019-08-19
Report number:	EF 19/08/2019/23; EF 12/12/2019/25
Length:	215 mm
Width:	60 mm
Height:	175 mm
IP rating:	IP 20
Protection class:	II
Dimmable:	No

Equipment

Test system:	EVERFINE GO-2000B_V1 SYSTEM V2.00.417
Temperature:	25 +/-1 °C
Humidity:	65.0%
γ interval:	2 deg
C interval:	10 deg
γ range:	0-180 deg
Measurement distance:	6.56 m

Nowodvorski sp. j.

ul. Bojemskiego 11, 42-202 Częstochowa, POLSKA, NIP: PL 5731015208


Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12

www.nowodvorski.com

Photometric data

Total luminous flux:	1395.89 lm
Color temperature:	3931 K
x:	0.3866
y:	0.3895
Color rendering index:	92.1
Wattage:	16.748 W
U	230.48 V
I	0.0789 A
Power factor:	0.9290
Luminous efficacy:	83.42 lm/W
Flux in lower hemisphere:	98.6%
Flux in upper hemisphere:	1.4%
Maximum luminous intensity:	6668 cd
Light output ratio (LOR):	100.00%

Beam cone diagram Beam angle 24°




Nowodvorski sp. j.

ul. Bojemskiego 11, 42-202 Częstochowa, POLSKA, NIP: PL 5731015208

Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12


www.nowodvorski.com

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Luminous intensity [cd]
C0-C180 ————
C90-C270 ————

Spectral distribution



Nowodvorski sp. j.

ul. Bojemskiego 11, 42-202 Częstochowa, POLSKA, NIP: PL 5731015208

Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12

www.nowodvorski.com